









SECTION A-A



备注:

1. 未注圆角为R0.05-0.2MM;
2. 最大毛边允许0.05MM;
3. 端子平面度: 0.10MM MAX;
4. 产品符合ROHS环保要求;
5. PIN针拉力: 1.0KG Min.

REV	DATE	REVISIONS REC




东莞市福讯达塑胶制品有限公司

DONGGUAN FU XUN DA PLASTICS PRODUCTS CO., LTD

地址: 东莞市横沥镇三江工业区116栋

TEL: 0769-82218739 82218769 FAX: 0769-82218929

DRAFTER	ZHANG SHAO YONG	TOLERANCE	DATE:
CHECK	CHEN YONG LONG	0<L≤4 ±0.1	2025.04.17
APPROVED	ZHU DONG SHENG	4<L≤16 ±0.2	
		16<L≤50 ±0.3	
		PIN PITCH ±0.2	



DRAWING TITLE: EP10	TERMIAL DIMENTION: ----	ANGLE: ±1°
MODLE NAME: FX-1003-2	TERMINAL MATERIAL: PB WIRE	UNIT: mm
SPECIFICATION: 4+4 PIN	UL RATING: 94V-0	SCALE: 1 : 1
BOBBING MATERIAL: PM9630	PULLING STRENGTH: 1.0KG/MIN	REV: A/0